

INDUSTRIAL COMPONENT DATA

2170207 UNITRONIC BUS IBS Yv 3X2X0,22 LAPP UNITRONIC BUS IBS Yv 3X2X0,22

Brand: LAPP | Manufacturer Part Number: 2170207



Manufacturer	LAPP
MPN / Reference	2170207
Catalog number	UNITRONIC BUS IBS Yv 3X2X0,22
Category	Data and communication cable
Minimum order	1 m.
Document ID	EO-5ABDF81CD4
Generated	2026-08-05

Product Overview

UNITRONIC BUS IBS Yv 3X2X0,22

UNITRONIC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > UNITRONIC BUS cabling
--------------	------------------------------

Additional Product Information

Remote + installation remote bus cable. PUR outer sheath, halogen free, flame retardant, core identification code DIN 47100. Temp. range from -30°C bis +80°C

Benefits

Applications:fixed Installation, high flexible use, outdoor use/direct burial

Application range

Remote bus/ installation remote bus cable

Product features

UNITRONIC®

BUS IBS

fixed installation

UNITRONIC®

BUS IBS Combi

with power supply

UNITRONIC®

BUS IBS A
UL-verified
UNITRONIC®
BUS Yv
outdoor use/ direct burial
UNITRONIC®
BUS Yv Combi
with power supply
UNITRONIC®
BUS IBS FD P
fixed installation
UNITRONIC®
BUS IBS FD P Combi
with power supply
UNITRONIC® BUS IBS FD P Combi A
UL-verified
Norm references / Approvals
Refer to data sheet for more details
According to DIN EN 61158
Product Make-up
See data sheet
Classification ETIM 5
ETIM 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable
Classification ETIM 6
ETIM 6.0 Class-ID: EC000830
ETIM 6.0 Class-Description: Data cable
Peak operating voltage
(not for power applications) 250 V
Conductor resistance
see data sheet
Minimum bending radius
Fixed installation: 8 x outer diameter
Flexing: 15 x outer diameter
Test voltage
Core/core: 1500 V rms
Characteristic impedance
100 Ohm
Temperature range
UNITRONIC®
BUS IBS
fixed installation: -30°C to +80°C
flexing: -5°C to +70°C
UNITRONIC®
BUS IBS FD P
fixed installation: -40°C to +80°C
flexing: -5°C to +70°C

UNITRONIC®

BUS IBS Yv

Fest verlegt: -40°C bis +70°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend LAPP / 2170207 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.