

## INDUSTRIAL COMPONENT DATA

# 2170230 UNITRONIC BUS ASI (TPE) 2X1,5 YE LAPP

## UNITRONIC BUS ASI (TPE) 2X1,5 YE

Brand: LAPP | Manufacturer Part Number: 2170230

LAPP KABEL STUFGART UNITRONIC® BUS ASI

|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | LAPP                             |
| MPN / Reference | 2170230                          |
| Catalog number  | UNITRONIC BUS ASI (TPE) 2X1,5 YE |
| Category        | Data and communication cable     |
| Minimum order   | 1 m.                             |
| Document ID     | EO-354740FF2A                    |
| Generated       | 2026-08-04                       |

### Product Overview

UNITRONIC BUS ASI (TPE) 2X1,5 YE  
UNITRONIC

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path LAPP > UNITRONIC BUS cabling

### Additional Product Information

Communication at sensor/actuator level. Halogen free (rubber), UL-approval (PVC), oil resistant (TPE). Temperature range from -40°C bis +90°C

"LD" = Long Distance

Benefits

The new BUS ASI LD 2 x 2.5 (Long Distance) allows even modules located further away to be connected.

AS-I power supplies can be reduced. The BUS ASI LD is downwards-compatible with version 1.5.

The rubber versions are halogen-free

Application range

Communication at sensor/actuator level

Sensor-/actuator wiring

For fixed installation as well as occasional flexing at free, non-continuously recurring movement without tensile load

The TPE version has an oil-resistant outer sheath. It is suitable for wet areas, in particular in conjunction with water-soluble cooling lubricants.

Product features

Data and power are transmitted via an unscreened, geometrically coded two-core flat cable (protection against polarity reversal).

The conductor is contacted by "piercing technology" within the ASI modules.

The sensors are connected to the ASI modules (coupling modules) using round cables (connection cables).

Norm references / Approvals

ASI is standardised Europe-wide in EN 50295 and internationally in IEC 62026-2.

PVC A version with UL/CSA (CMX) certification

UL/CSA version: CMG c(UL)us or (UL)CL2 or AWM 300V FT4 certified

Product Make-up

Conductor: fine-wire tinned-copper strands

Core insulation: blue and brown

Outer sheath:

rubber (G), halogenfree

thermoplastic elastomers (TPE)

PVC

Outer sheath: yellow (RAL 1023), black...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 2170230 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.