


INDUSTRIAL COMPONENT DATA

2170634 UNI LAN1000 S/FTP Cat.7 dup 2x (4x2xAWG23/1) LAPP UNILAN1000S/FTPCat.7dup 2x(4x2xAWG23/1)

Brand: LAPP | Manufacturer Part Number: 2170634



Manufacturer	LAPP
MPN / Reference	2170634
Catalog number	UNI LAN1000 S/FTP Cat.7 dup 2x (4x2xAWG23/1)
Category	Data and communication cable
Minimum order	100 m.
Document ID	EO-CA88AE7C00
Generated	2026-08-05

Product Overview

UNILAN1000S/FTPCat.7dup 2x(4x2xAWG23/1)

UNITRONIC® LAN 1000 Cat.7

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > UNITRONIC LAN cabling
--------------	------------------------------

Additional Product Information

The LAN cable can be used in places with a high density of terminal devices, for example in administrative buildings. It transmits the digital and analogue signals.

CPR: Article number choice under www.lappkabel.com/cpr

Benefits

LAN cables for structured building cabling according to EN 50173 and ISO/IEC 11801

Application range

Mainly used where the terminal density is very high, e.g. for wiring office, administration and development buildings in the tertiary area (floor wiring).

Cable length in tertiary area (horizontal area, floor) should not exceed a length of 100 m in accordance with the ISO/IEC 11801 and EN 50173 standards (90 m in cable duct + 10 m in working area)

Product features

Transfer of digital and analogue data signals

Flame-retardant according to IEC 60332-1-2 and bundle flame test according to IEC 60332-3-24

IEEE 802.3: 10/100/1000Base-T, 10GBase-T

IEEE 802.5: ISDN; FDDI; ATM; cable sharing

IEEE 802.3at: suitable for PoE

Norm references / Approvals

Class F in the ISO/IEC 11801 standard corresponds to CAT.7

Product Make-up

Solid conductor

S/FTP: copper braid as overall screening and pair screening with aluminium compound foil

Outer sheath: halogen-free, flame-retardant compound

Colour: yellow (RAL 1021)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000830

ETIM 5.0 Class-Description: Data cable

Classification ETIM 6

ETIM 6.0 Class-ID: EC000830

ETIM 6.0 Class-Description: Data cable

Minimum bending radius

during installation: 8 x outer diameter

Fixed installation:....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 2170634 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.