

**INDUSTRIAL COMPONENT DATA**

# 2171035 IE-PNB-5-M12D-S-10-Y-2-22-7-OE LAPP

## IE-PNB-5-M12D-S-10-Y-2-22-7-OE

Brand: LAPP | Manufacturer Part Number: 2171035



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | LAPP                                      |
| MPN / Reference | 2171035                                   |
| Catalog number  | IE-PNB-5-M12D-S-10-Y-2-22-7-OE            |
| Category        | Patch cord copper (twisted pair) industry |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-9FD105F20E                             |
| Generated       | 2026-08-04                                |

### Product Overview

IE-PNB-5-M12D-S-10-Y-2-22-7-OE  
ETHERLINE

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      LAPP &gt; ETHERLINE Patchcords

### Additional Product Information

**Benefits**

Non-permanent connections allow for easy change of equipment  
For directly connecting two electric components

**Application range**

Flexible use  
suitable for EtherCAT and EtherNet/IP applications  
Suitable for use in industrial applications

For indoor use

**Product features**

Meets the requirements according to Cat. 5e and class D  
2pair: 10/100 Mbit/s for Industrial Ethernet

**Norm references / Approvals**

The cable is UL/CSA-certified (CMG)  
UL File Number: E249137

**Product Make-up**

Braided conductor, 2x2x AWG22/7

Star quad

Overall screening with copper braid and plastic-laminated aluminium foil

Outer sheath made of PVC

Colour: green (based on RAL 6018)

Pre-assembled connection and patch cable with M12 D-coded connectors with vibration protection

4 pole M12 connector with vibration protection

Classification ETIM 5

ETIM 5.0 Class-ID: EC002599

ETIM 5.0 Class-Description: Patch cord copper (twisted pair) industry

Classification ETIM 6

ETIM 6.0 Class-ID: EC002599

ETIM 6.0 Class-Description: Patch cord copper (twisted pair) industry

Minimum bending radius

Flexing: 15 x outer diameter

Fixed installation: 10 x outer diameter

Protection rating

IP69

Temperature range

Flexing: -20°C to +60°C

Fixed installation: -40°C to +80°C

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send LAPP / 2171035 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.