

INDUSTRIAL COMPONENT DATA

2171064 IE-PNC-5-M12D-A-5-P-2-22-FD-M12D-S LAPP

IE-PNC-5-M12D-A-5-P-2-22-FD-M12D-S

Brand: LAPP | Manufacturer Part Number: 2171064



Manufacturer	LAPP
MPN / Reference	2171064
Catalog number	IE-PNC-5-M12D-A-5-P-2-22-FD-M12D-S
Category	Patch cord copper (twisted pair) industry
Minimum order	1 Pcs
Document ID	EO-D5F7B1ACF9
Generated	2026-08-01

Product Overview

IE-PNC-5-M12D-A-5-P-2-22-FD-M12D-S
ETHERLINE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > ETHERLINE Patchcords

Additional Product Information

Industrial Ethernet Profinet Type C, Patchcord M12/M12, D-code, straight or angled, PUR; UL- approval; Cat.5 2pair
Based on 2170894

Additional variants are available at
www.lappgroup.com/assemblyfinder
or on request.

Benefits

For directly connecting two electric components
Non-permanent connections allow for easy change of equipment

Application range

Highly flexible application
suitable for EtherCAT and EtherNet/IP applications
Suitable for use in industrial applications

For indoor use

Product features

Meets the requirements according to Cat. 5e and class D

2pair: 10/100 Mbit/s for Industrial Ethernet

Norm references / Approvals

The cable is UL/CSA-certified (CMX)

UL File Number: E249137

Product Make-up

Braided conductor, 2x2x AWG22/7

Star quad

Overall screening with copper braid and plastic-laminated aluminium foil

Outer sheath made of PUR

Colour: green (based on RAL 6018)

Pre-assembled connection and patch cable with M12 D-coded connectors with vibration protection

4 pole M12 connector with vibration protection

Classification ETIM 5

ETIM 5.0 Class-ID: EC002599

ETIM 5.0 Class-Description: Patch cord copper (twisted pair) industry

Classification ETIM 6

ETIM 6.0 Class-ID: EC002599

ETIM 6.0 Class-Description: Patch cord copper (twisted pair) industry

Minimum bending radius

Moved: 10 x outer diameter

Protection rating

IP69

Temperature range

Flexing: -20°C to +60°C

Fixed installation: -30°C to +70°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 2171064 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.