


**INDUSTRIAL COMPONENT DATA**

# 22260582 AB-C3- 5,0PUR-C-1L-S LAPP AB-C3- 5,0PUR-C-1L-S

Brand: LAPP | Manufacturer Part Number: 22260582



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | LAPP                       |
| MPN / Reference | 22260582                   |
| Catalog number  | AB-C3- 5,0PUR-C-1L-S       |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-085856EF2D              |
| Generated       | 2026-08-05                 |

## Product Overview

AB-C3- 5,0PUR-C-1L-S  
UNITRONIC® SENSOR Valve

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                 |
|--------------|---------------------------------|
| Catalog path | LAPP > Fieldbus Modules passive |
|--------------|---------------------------------|

## Additional Product Information

**Benefits**

Cost-saving due to quick and easy installation

Space-saving due to compact dimensions.

Fast and easy error tracking

**Product features**

Suitable for drag chains

With protective circuit (Z diode), PE-bridged (except type AD)

With LED status indicator (yellow)

With display switch state (2 LEDs, red/green)

Including tag carrier

PWIS-free

**Product Make-up**

3 or 5 x 0.5 mm²

Core identification code:

Black cores with white numbers +green/yellow

Outer sheath: PUR halogen-free, black

Outer diameter:

4.5 mm (3 pins)

5.3 mm (5 pins)

Classification ETIM 5

ETIM 5.0 Class-ID: EC001855

ETIM 5.0 Class-Description: Sensor-actuator patch cord

Classification ETIM 6

ETIM 6.0 Class-ID: EC001855

ETIM 6.0 Class-Description: Sensor-actuator patch cord

Material

Contact: CuSn

Contact surface: Ag

Protection rating

IP65/IP67

Ambient temperature (operation)

Valve connector -20°C to +85°C

Fixed installation -40°C to +80°C

Flexing -20°C to +80°C

Rated current (A)

4 A

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 22260582 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.