

**INDUSTRIAL COMPONENT DATA**

# 22260600 AB-C3-M12Y-2XM12FS B E LAPP

## AB-C3-M12Y-2XM12FS B E

Brand: LAPP | Manufacturer Part Number: 22260600



|                 |                         |
|-----------------|-------------------------|
| Manufacturer    | LAPP                    |
| MPN / Reference | 22260600                |
| Catalog number  | AB-C3-M12Y-2XM12FS B E  |
| Category        | Sensor actuator adapter |
| Minimum order   | 5 Pcs                   |
| Document ID     | EO-CC3EA31A96           |
| Generated       | 2026-08-03              |

### Product Overview

AB-C3-M12Y-2XM12FS B E  
EPIC® SENSOR M8Y M12Y

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                 |
|--------------|---------------------------------|
| Catalog path | LAPP > Fieldbus Modules passive |
|--------------|---------------------------------|

### Additional Product Information

Y-distributor, M12, M8, 3-pole, 4-pole, 5-pole, parallel distributor, bridged, A-coded, IP65/IP67

**Benefits**

Cost-saving due to quick and easy installation

Space-saving due to compact dimensions

Fast and easy error tracking

**Product features**

Design: Plug on 2x socket

M12 design with screw hole

PWIS-free

**Product Make-up**

22260600:

M12, 3-pin+ PE, straight M12 plug on 2x straight M12 socket, pin 2+4 bridged

22260601:

M12, 3-pin+ PE, straight M12 plug on 2x straight M12 socket

22260602:

M12, 5-pin straight M12 plug on 2x 3-pin straight M8 socket, parallel distributor

22260603:

M8, 4-pin M8 plug on 2x 3pin M8 socket

22260604:

M8 plug on M8 socket, 3-pin parallel distributor

Classification ETIM 5

ETIM 5.0 Class-ID: EC002062

ETIM 5.0 Class-Description: Sensor-actuator adapting connector

Classification ETIM 6

ETIM 6.0 Class-ID: EC002062

ETIM 6.0 Class-Description: Sensor-actuator connector

Material

Contact: CuZn

Contact surface: Ni/Au

Knurl: Zinc die-cast, nickel-plated

Gripping body: TPU, flame-retardant, self-extinguishing

Protection rating

IP65/IP67

Ambient temperature (operation)

Plug/socket -25°C to +90°C

Coding

A-standard

Rated current (A)

4 A

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 22260600 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.