

INDUSTRIAL COMPONENT DATA

22260792 AB-DN-2,0PUR-M12FS LAPP AB-DN-2,0PUR-M12FS

Brand: LAPP | Manufacturer Part Number: 22260792



Manufacturer	LAPP
MPN / Reference	22260792
Catalog number	AB-DN-2,0PUR-M12FS
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-77565AC070
Generated	2026-07-31

Product Overview

AB-DN-2,0PUR-M12FS
UNITRONIC® BUS CAN M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > Fieldbus Modules passive
--------------	---------------------------------

Additional Product Information

Robust, pre-assembled DeviceNet M12 (A-coded) cable with PUR (halogen-free) outer sheath for flexible use (drag chain).
Shielded version.

Other types are available at
www.lappgroup.com/assemblyfinder
or on request

Benefits

Cost-effective, efficient wiring of fieldbus and sensor/ actuator installations
Space-saving due to compact dimensions
Fast and easy error tracking

Robust design

Application range

Mechanical and plant engineering

Product features

5-core DeviceNet/CANopen cable, shielded
M12 connector, A-coded with quick-locking system

Suitable for drag chains

Including tag carrier

Norm references / Approvals

UL-AWM-Style 21198 (80 °C / 300 V)

Product Make-up

Signal line: 2 x 0.25 mm²

Power supply: 2 x 0.34 mm²

Drain wire: 1 x 0.34 mm²

Core colours: red/black, blue/white

Outer sheath: PUR halogen-free, violett

Outer diameter: 6.7 mm

Shielded version

Classification ETIM 5

ETIM 5.0 Class-ID: EC001855

ETIM 5.0 Class-Description: Sensor-actuator patch cord

Classification ETIM 6

ETIM 6.0 Class-ID: EC001855

ETIM 6.0 Class-Description: Sensor-actuator patch cord

Material

Contact: CuSn

Contact surface: Ni/Au

Knurl: Zinc die-cast, nickel-plated

Gripping body: TPU, flame-retardant, self-extinguishing

Protection rating

IP65/IP67

Ambient temperature (operation)

Plug/socket -25°C to +90°C

Fixed installation -40°C to +80°C

Flexing -20°C to +70°C

Coding

A-standard

Rated current (A)

4 A

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 22260792 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.