

**INDUSTRIAL COMPONENT DATA**

# 22260845 AB-C4-5,0PVC-M8FA LAPP AB-C4-5,0PVC-M8FA

Brand: LAPP | Manufacturer Part Number: 22260845



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | LAPP                       |
| MPN / Reference | 22260845                   |
| Catalog number  | AB-C4-5,0PVC-M8FA          |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-5082A91CE0              |
| Generated       | 2026-07-28                 |

## Product Overview

AB-C4-5,0PVC-M8FA  
UNITRONIC® SENSOR PVC M8

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                 |
|--------------|---------------------------------|
| Catalog path | LAPP > Fieldbus Modules passive |
|--------------|---------------------------------|

## Additional Product Information

Sensor/actuator connecting cable 3-, 4-pin, M8 connector/M8 socket on free cable end, A-coded, PVC, IP65/IP67/IP68

Other types are available at

[www.lappgroup.com/assemblyfinder](http://www.lappgroup.com/assemblyfinder)

or on request

Benefits

Cost-saving due to quick and easy installation

Space-saving due to compact dimensions

Fast and easy error tracking

Application range

For medium mechanical stress in dry conditions

Product features

Partly oil and chemical resistant

PWIS-free

Including tag carrier

Norm references / Approvals

Flame-retardant according to style 2464

UL File Number: E249137

Product Make-up

Core cross section: 0.25 mm<sup>2</sup>

Colour-code:

3-pin: bn (1), bu (3), bk (4)

4-pin: bn (1), wh (2), bu (3), bk (4)

Outer sheath: PVC, black

Classification ETIM 5

ETIM 5.0 Class-ID: EC001855

ETIM 5.0 Class-Description: Sensor-actuator patch cord

Material

Contact: CuSn

Contact surface: Ni/Au

Knurl: Zinc die-cast, nickel-plated

Gripping body: TPU, flame-retardant, self-extinguishing

Protection rating

IP65/IP67/IP68

Ambient temperature (operation)

Plug/socket -25°C to +90°C

Fixed installation -25°C to +80°C

Flexing -5°C to +80°C

Coding

A-standard

Rated current (A)

4 A

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 22260845 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.