

**INDUSTRIAL COMPONENT DATA**

# 44420128 EPIC SIGNAL M23 17E S D-Sub LAPP EPIC SIGNAL M23 17E S D-Sub (5)

Brand: LAPP | Manufacturer Part Number: 44420128



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | LAPP                                      |
| MPN / Reference | 44420128                                  |
| Catalog number  | EPIC SIGNAL M23 17E S D-Sub               |
| Category        | Contact insert for rectangular connectors |
| Minimum order   | 5 Pcs                                     |
| Document ID     | EO-85F4554CF8                             |
| Generated       | 2026-08-01                                |

## Product Overview

EPIC SIGNAL M23 17E S D-Sub (5)  
EPIC® SIGNAL M23 Inserts 17 pole D-Sub

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                   |
|--------------|-------------------|
| Catalog path | LAPP > EPIC Round |
|--------------|-------------------|

## Additional Product Information

EPIC® M23 Inserts 17 pole for D-Sub contacts on reel for M23 circular connector series  
for D-Sub ribbon contacts  
for automated production with crimping machine  
Made in Germany  
Benefits  
Efficient assembling due to the use of D-Sub contacts-on-reel  
Application range  
Plant engineering  
Measurement and control technology  
Apparatus construction  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000438  
ETIM 5.0 Class-Description: Contact insert for industrial connectors  
Classification ETIM 6

ETIM 6.0 Class-ID: EC000438

ETIM 6.0 Class-Description: Contact insert for industrial connectors

Rated voltage (V)

according to IEC 61984: 50 V

Rated impulse voltage

0,8 kV

Rated current (A)

4 A

Pollution degree

3

Contact resistance

< 4 mOhm

Contacts

Partly gold-plated brass

Number of contacts

17

17\*1mm D-Sub contacts

Termination methods

Crimp termination: 0.08 - 0.56 mm<sup>2</sup>

Cycle of mechanical operation

50

Temperature range

-25°C up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 44420128 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.