

INDUSTRIAL COMPONENT DATA

44423207 EPIC H-BE 24 BP LAPP EPIC H-BE 24 BP

Brand: LAPP | Manufacturer Part Number: 44423207



Manufacturer	LAPP
MPN / Reference	44423207
Catalog number	EPIC H-BE 24 BP
Category	Contact insert for rectangular connectors
Minimum order	5 Pcs
Document ID	EO-5590D73AF4
Generated	2026-08-02

Product Overview

EPIC H-BE 24 BP
EPIC® H-BE 24 Push-In termination

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > EPIC rectangular

Additional Product Information

The multi-functional insert for various applications can be used for higher voltages and currents and is highly reliable.

Push-In version - fast and easy tool free connection technology

Screw, crimp, cage clamp and Push-In version - freely combinable

Multifunctional insert for versatile applications

Benefits

Insertion of cores with end sleeves in Push-In inserts gives mounting safety and time saving without any tools

Easy dismantling and insertion of wires by pushing the orange button

Test socket for standard 2mm test tip for easy testing of Push-In inserts

Railway applications

- Fire protection on railway vehicles: Test according to EN 45545-2. Requirement sets R22 and R23. Hazard level HL1, HL2 and HL3

The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents

Application range

Mechanical engineering

Plastics industry
Light & sound technology
Railway applications / vehicle construction
Classification ETIM 5
ETIM 5.0 Class-ID: EC000438
ETIM 5.0 Class-Description: Contact insert for industrial connectors
Classification ETIM 6
ETIM 6.0 Class-ID: EC000438
ETIM 6.0 Class-Description: Contact insert for industrial connectors
Rated voltage (V)
IEC: 500 VUL: 600 VCSA: 600 V
Rated impulse voltage
6 kV
Rated current (A)
IEC: 16 A
UL: 13 A
CSA: 13 A
Pollution degree
3
Flammability
UL94 V-0
Contact resistance
< 2 mOhm
Contacts
Copper alloy, hard silver-plated
Number of contacts
24 + PE
Termination methods
Push-In ter...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 44423207 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.