

**INDUSTRIAL COMPONENT DATA**

# 52005170 SKINDICHT SHVE PG 21/21/18/15 LAPP SKINDICHT SHVE PG 21/21/18/15

Brand: LAPP | Manufacturer Part Number: 52005170



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LAPP                          |
| MPN / Reference | 52005170                      |
| Catalog number  | SKINDICHT SHVE PG 21/21/18/15 |
| Category        | Cable gland                   |
| Minimum order   | 25 Pcs                        |
| Document ID     | EO-6404BEA60F                 |
| Generated       | 2026-08-06                    |

## Product Overview

SKINDICHT SHVE PG 21/21/18/15

SKINDICHT® SHVE

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SKINDICHT cabling

## Additional Product Information

SKINDICHT® SHVE, PG cable gland with low-resistance 360° screen contact and high degree of protection, as earthing gland

Benefits

Optimum, low-resistance 360° screen contact

High degree of protection

High strain relief

Application range

Earthing gland, for applications where electrical interference fields can occur.

Medical engineering

Frequency converters

Airports

Measurement and control technology

Product Make-up

1 fitting

2 earth sleeves

3 sealing cones

4 cone, brass

5 compression screws

Note

Counter nut to be used: SKINDICHT® SM

EMC counter nut, SKINDICHT® SM nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Example order identification:

SHVE 13.5 / 9 / 9 / 5

13.5 = PG thread compression screw

9 = PG connection thread

9 = Clear width of sealing cone

5 = Clear width earthing sleeve

Classification

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

The installation dimensions  
can be found in appendix T21

Material

Body: nickel-plated

Earthing sleeve: blank brass

Special sealing cone: CR

O-ring: NBR

Protection rating

IP 68 - 10 bar

Temperature range

-20°C to +80°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 52005170 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.