

INDUSTRIAL COMPONENT DATA

52105720 SKINDICHT SRE-M 40x1,5/36/30/24 LAPP

SKINDICHT SRE-M 40x1,5/36/30/24

Brand: LAPP | Manufacturer Part Number: 52105720



Manufacturer	LAPP
MPN / Reference	52105720
Catalog number	SKINDICHT SRE-M 40x1,5/36/30/24
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-181D8E0221
Generated	2026-08-06

Product Overview

SKINDICHT SRE-M 40x1,5/36/30/24
SKINDICHT® SRE-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINDICHT cabling
--------------	--------------------------

Additional Product Information

SKINDICHT® SRE-M, metric cable gland with perfect seal with anti-kink protection, high degree of protection and cable-protecting strain relief

Benefits

Perfect seal with anti-kink protection

Optimum, low-resistance 360° screen contact

Cable-protecting strain relief

Gentle cable clamping

High degree of protection

Application range

Earthing gland with additional anti-kink protection. For applications where electrical interference fields can occur.

Moving machine parts

Conveyor and transport systems

Production lines

Measurement and control technology

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Example description:

SRE-M 20/13.5/9/6

20 = metric connection thread

13.5 = PG function thread

9 = clear opening of anti-kink sleeve (F)

6 = clear opening of earthing sleeve (B)

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

The installation dimensions

can be found in appendix T21

On request

Available with long connection thread

Material

Body: nickel-plated brass

Earthing sleeve: plain brass

Anti-kink sleeve: CR/NBR

O-ring: NBR

Protection rating

IP 65

Temperature range

-20°C to +80°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 52105720 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.