

INDUSTRIAL COMPONENT DATA

52105860 SKINDICHT SR-SV-M 20x1,5/13,5/13 LAPP

SKINDICHT SR-SV-M 20x1,5/13,5/13

Brand: LAPP | Manufacturer Part Number: 52105860



Manufacturer	LAPP
MPN / Reference	52105860
Catalog number	SKINDICHT SR-SV-M 20x1,5/13,5/13
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-09AA37EAAD
Generated	2026-08-05

Product Overview

SKINDICHT SR-SV-M 20x1,5/13,5/13

SKINDICHT® SR-SV-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > SKINDICHT cabling

Additional Product Information

SKINDICHT® SR-SV-M, robust, metric cable gland for high temperatures, seawater-resistant and resistant to oils, acids and chemicals

Benefits

For high temperatures

Resistant to oils, solvents, acids and chemicals

Seawater-resistant

High strain relief

Robust

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Special cable gland with FKM anti-kink sleeve. Our own reinforced acid-resistant FKM receptacle does not show any effects of aging even after an extended period of use at a temperature of +165°C.

Machine and turbine manufacturing

Power plant engineering

Laboratory

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

Counter nut to be used: SKINDICHT® SM-M

EMC version is available upon request

Example description:

SR-SV-M 20/11/7

20 = metric connection thread

11 = PG function thread

7 = clear opening of seal

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

The installation dimensions

can be found in appendix T21

On request

Available with long connection thread

Material

Body: nickel-plated brass

O-ring: FKM

Anti-kink protection: FKM

Protection rating

IP 65

Temperature range

-20°C to +165°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 52105860 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.