

**INDUSTRIAL COMPONENT DATA**

# 53018010 SKINTOP ST PG 9 RAL 7035 LGY LAPP SKINTOP ST PG 9 RAL 7035 LGY

Brand: LAPP | Manufacturer Part Number: 53018010



|                 |                              |
|-----------------|------------------------------|
| Manufacturer    | LAPP                         |
| MPN / Reference | 53018010                     |
| Catalog number  | SKINTOP ST PG 9 RAL 7035 LGY |
| Category        | Cable gland                  |
| Minimum order   | 100 Pcs                      |
| Document ID     | EO-D1E381F6CE                |
| Generated       | 2026-08-02                   |

## Product Overview

SKINTOP ST PG 9 RAL 7035 LGY  
SKINTOP® ST

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SKINTOP cabling

## Additional Product Information

SKINTOP® ST, increased oil-resistant polyamide cable gland with variable clamping ranges, permanent vibration protection and strain relief

**Benefits**

High oil-resistance for maximum reliability

Permanent vibration protection

Optimum strain relief

Wide, variable clamping ranges

Various accessories (e.g. multiple sealing inserts)

**Application range**

Used in areas where a lot of cables and wires need to be inserted into housings with minimum space requirements

Machine and equipment manufacturing

Photovoltaic

Automation technology

Norm references / Approvals

UL File Nr. E79903

Product Make-up

PG connection thread acc. to DIN 40430

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to Appendix T21 for the installation dimensions and torques

Colour delivered

Silver grey (RAL 7001)

Light grey (RAL 7035)

Black (RAL 9005), UV-resistant

Material

Body: Polyamide

Seal: CR

Tests

GGVS: TÜ.EGG.020-95

Protection rating

IP 68 - 5 bar

NEMA Type 1, 12

Temperature range

Dynamic: -20°C to +100°C

Fixed: -40°C to +100°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53018010 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.