

INDUSTRIAL COMPONENT DATA

53111710 SKINTOP BS-M 16x1,5 RAL 9005 BK LAPP SKINTOP BS-M 16x1,5 RAL 9005 BK

Brand: LAPP | Manufacturer Part Number: 53111710



Manufacturer	LAPP
MPN / Reference	53111710
Catalog number	SKINTOP BS-M 16x1,5 RAL 9005 BK
Category	Cable gland
Minimum order	100 Pcs
Document ID	EO-153B392EAD
Generated	2026-08-06

Product Overview

SKINTOP BS-M 16x1,5 RAL 9005 BK
SKINTOP® BS-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® BS-M, plastic cable gland with bending and anti-kink protection, to protect flexible cables, for moving machine parts

Benefits

Reliable bending and anti-kink protection

Cable conservation

Functional reliability

To protect flexible cables

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Handheld device

Robotics industry

Light and sound applications

Moving machine parts

Norm references / Approvals

UL File Nr. E79903

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

Version with reducing insert to seal smaller cable cross-sections SKINTOP® BSR-M on request

SKINTOP® BS M ISO versions with extra-long connection thread, see table, no DNV approval

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to Appendix T21 for the installation dimensions and torques

On request

with reducing sealing ring

Colour delivered

Silver grey (RAL 7001)

Light grey (RAL 7035)

Black (RAL 9005), UV-resistant

Material

Body: Polyamide

Seal: CR

Protection rating

IP 68 - 5 bar

NEMA Type 1, 12

Temperature range

-20°C to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53111710 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.