

INDUSTRIAL COMPONENT DATA

53112020 SKINTOP MS-M 20x1,5 LAPP SKINTOP MS-M 20x1,5

Brand: LAPP | Manufacturer Part Number: 53112020



Manufacturer	LAPP
MPN / Reference	53112020
Catalog number	SKINTOP MS-M 20x1,5
Category	Cable gland
Minimum order	50 Pcs
Document ID	EO-E9F01FB16C
Generated	2026-08-01

Product Overview

SKINTOP MS-M 20x1,5

SKINTOP® MS-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > SKINTOP cabling

Additional Product Information

SKINTOP® MS-M, brass cable gland for cable diameters up to 98mm, in areas where mechanical and chemical stability are critical

Also available as lead-free version - the lead-free articles end on LF after the article number

SKINTOP® MS-M sizes 75 x 1.5 to 110 x 2 with innovative double lamella gasket for easier assembling of cables with large diameters.

With IP69 approval! Proven to withstand the most demanding cleaning procedures for industrial machinery with high-pressure cleaners and hot water!

Benefits

Maximum reliability

Optimum strain relief

Wide, variable clamping ranges

Application range

In areas where mechanical and chemical stability are critical

Chemical industry

Measurement and control technology

Machine and equipment manufacturing
Plant engineering
Norm references / Approvals
UL File Nr. E79903
Product Make-up
Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444
Classification ETIM 5
ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland
Classification ETIM 6
ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class-Description: Cable screw gland
Caution
Refer to Appendix T21 for the installation dimensions and torques
Certifications
VDE, UL and DNV approval available up to size M75x1,5
Material
Body: nickel-plated brass
Insert: polyamide
Sealing: CR
O-ring: NBR
Protection rating
IP 68 - 10 bar
IP 69 (M12 - M63)
NEMA Type 1, 4x, 6, 12
Temperature range
Dynamic: -25°C up to +100°C
Fixed: -40°C to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112020 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.