

**INDUSTRIAL COMPONENT DATA**

# 53112230 SKINTOP MS-SC PG 13,5 LAPP SKINTOP MS-SC PG 13,5

Brand: LAPP | Manufacturer Part Number: 53112230



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | LAPP                  |
| MPN / Reference | 53112230              |
| Catalog number  | SKINTOP MS-SC PG 13,5 |
| Category        | Cable gland           |
| Minimum order   | 25 Pcs                |
| Document ID     | EO-AB5E265261         |
| Generated       | 2026-08-03            |

## Product Overview

SKINTOP MS-SC PG 13,5  
SKINTOP® MS-SC

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SKINTOP cabling

## Additional Product Information

SKINTOP® MS-SC, brass cable gland with low-resistance screen contact and highly conductive, flexible EMC contact, easy to assemble

**Benefits**

Low-resistance screen contact, optimum EMC protection

Suitable for cables with and without inner sheath

Also suitable for continuing the cable screen to another connection

Highly conductive, flexible EMC contact for clamping various screen diameters

Few operation steps, easy to assemble

**Application range**

For EMC-compliant earthing of the copper braiding

Telecommunication

Industrial machinery and plant engineering

Measurement and control technology

Automation technology

**Product Make-up**

PG connection thread acc. to DIN 40430

**Note**

EMC counter nut, SKINDICHT® SM nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

**Caution**

Refer to Appendix T21 for the installation dimensions and torques

**Material**

Body: nickel-plated brass

Insert: polyamide

Sealing: CR

O-ring: NBR

Protection rating

IP 68 - 5 bar

Temperature range

Dynamic: -25°C up to +100°C

Fixed: -40°C to +100°C

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send LAPP / 53112230 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.