

## INDUSTRIAL COMPONENT DATA

## 53112512 SKINTOP MS-M90 LAPP SKINTOP MS-M90

Brand: LAPP | Manufacturer Part Number: 53112512



|                 |                |
|-----------------|----------------|
| Manufacturer    | LAPP           |
| MPN / Reference | 53112512       |
| Catalog number  | SKINTOP MS-M90 |
| Category        | Cable gland    |
| Minimum order   | 1 Pcs          |
| Document ID     | EO-A6E0B27D4C  |
| Generated       | 2026-08-03     |

## Product Overview

SKINTOP MS-M90

SKINTOP® MS-M

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LAPP &gt; SKINTOP cabling

## Additional Product Information

SKINTOP® MS-M, brass cable gland for cable diameters up to 98mm, in areas where mechanical and chemical stability are critical

Also available as lead-free version - the lead-free articles end on LF after the article number

SKINTOP® MS-M sizes 75 x 1.5 to 110 x 2 with innovative double lamella gasket for easier assembling of cables with large diameters.

With IP69 approval! Proven to withstand the most demanding cleaning procedures for industrial machinery with high-pressure cleaners and hot water!

Benefits

Maximum reliability

Optimum strain relief

Wide, variable clamping ranges

Application range

In areas where mechanical and chemical stability are critical

Chemical industry

Measurement and control technology

Machine and equipment manufacturing  
Plant engineering  
Norm references / Approvals  
UL File Nr. E79903  
Product Make-up  
Metric connection thread acc. to DIN EN 60423  
Basis for technical information DIN IEC 62444  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000441  
ETIM 5.0 Class-Description: Cable screw gland  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000441  
ETIM 6.0 Class-Description: Cable screw gland  
Caution  
Refer to Appendix T21 for the installation dimensions and torques  
Certifications  
VDE, UL and DNV approval available up to size M75x1,5  
Material  
Body: nickel-plated brass  
Insert: polyamide  
Sealing: CR  
O-ring: NBR  
Protection rating  
IP 68 - 10 bar  
IP 69 (M12 - M63)  
NEMA Type 1, 4x, 6, 12  
Temperature range  
Dynamic: -25°C up to +100°C  
Fixed: -40°C to +100°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112512 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.