INDUSTRIAL COMPONENT DATA

53112536 SKINTOP MS-HF-M SC M50 LAPP SKINTOP MS-HF-M SC M50

Brand: LAPP | Manufacturer Part Number: 53112536

Manufacturer	LAPP
MPN / Reference	53112536
Catalog number	SKINTOP MS-HF-M SC M50
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-66A9FE2C99
Generated	2026-08-04

Product Overview

SKINTOP MS-HF-M SC M50
SKINTOP® MS-HF-M SC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling

Additional Product Information

SKINTOP® MS-SC-M, brass cable gland with low-resistance screen contact and highly conductive, flexible EMC contact, easy to assemble
Cable gland for railway applications
Hazard Level: HL 3
Benefits
Halogen-free and flame-retardant
Suitable for cables with and without inner sheath
Low-resistance screen contact, optimum EMC protection
Highly conductive, flexible EMC contact for clamping various screen diameters
Few operation steps, easy to assemble
Application range
Underground railways and trains
For EMC-compliant earthing of the copper braiding
Industrial machinery and plant engineering

Measurement and control technology
Automation technology
Norm references / Approvals
DIN EN 45545-2 (HL3)
DIN EN 45545-3 (E30)
Product Make-up
Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444
Note
SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings
Classification ETIM 5
ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland
Classification ETIM 6
ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class-Description: Cable screw gland
Caution
Refer to Appendix T21 for the installation dimensions and torques
Material
Body: nickel plated brass
Insert: halogen-free polyamid acc. to UL 94 V0
Sealing: special elastomer
O-ring: special elastomer
Protection rating
IP 68 - 5 bar
Temperature range
Dynamic: -25°C up to +100°C
Fixed: -40°C up to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112536 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.