

INDUSTRIAL COMPONENT DATA

53112640 SKINTOP MS-SC-M 25x1,5 LAPP SKINTOP MS-SC-M 25x1,5

Brand: LAPP | Manufacturer Part Number: 53112640



Manufacturer	LAPP
MPN / Reference	53112640
Catalog number	SKINTOP MS-SC-M 25x1,5
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-28A651838B
Generated	2026-07-29

Product Overview

SKINTOP MS-SC-M 25x1,5
SKINTOP® MS-SC-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® MS-SC-M, brass cable gland with low-resistance screen contact and highly conductive, flexible EMC contact, easy to assemble

Also available as lead-free version - the lead-free articles end on LF after the article number

Benefits

Low-resistance screen contact, optimum EMC protection

Suitable for cables with and without inner sheath

Also suitable for continuing the cable screen to another connection

Highly conductive, flexible EMC contact for clamping various screen diameters

Few operation steps, easy to assemble

Application range

For EMC-compliant earthing of the copper braiding

Telecommunication

Industrial machinery and plant engineering

Measurement and control technology

Automation technology

Norm references / Approvals

UL File Nr. E79903

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to Appendix T21 for the installation dimensions and torques

Note

In stainless steel V2A available

Material

Body: nickel-plated brass

Insert: polyamide

Sealing: CR

O-ring: NBR

Protection rating

IP 68 - 10 bar

IP 69

NEMA Type 1, 4x, 6, 12

Temperature range

Dynamic: -25°C up to +100°C

Fixed: -40°C up to t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112640 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.