

INDUSTRIAL COMPONENT DATA

53112681 SKINTOP MS-M BRUSH 63x1,5 plus LAPP SKINTOP MS-M BRUSH 63x1,5 plus

Brand: LAPP | Manufacturer Part Number: 53112681



Manufacturer	LAPP
MPN / Reference	53112681
Catalog number	SKINTOP MS-M BRUSH 63x1,5 plus
Category	Cable gland
Minimum order	1 Pcs
Document ID	EO-0418A695C9
Generated	2026-07-29

Product Overview

SKINTOP MS-M BRUSH 63x1,5 plus
SKINTOP® MS-M BRUSH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® MS-M BRUSH, brass cable gland with double lamella gasket, faster, low resistance 360° screen contact, simple assembling

NEW: Now also available in size M20x1.5

SKINTOP® MS-M sizes 75 x 1.5 to 110 x 2 with innovative double lamella gasket for easier assembling of cables with large diameters.

Benefits

Optimum, low-resistance 360° screen contact

Faster than any other comparable system

Also suitable for continuing the cable screen to another connection

Uncomplicated and reliable

Maximum assembly freedom during adjustment

Application range

For EMC-compliant earthing of the copper braiding

Automation systems

High-power drives

Frequency converters

Conveyor and transport systems

Norm references / Approvals

UL File Nr. E79903

UL approval for SKINTOP MS-M BRUSH M 20 x 1,5 up to M 75 x 1,5 plus and SKINTOP MS-M BRUSH 20 x 1,5 XL

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to Appendix T21 for the installation dimensions and torques

Material

Body: nickel-plated brass

Cap nut: nickel-plated brass

Insert: polyamide

EMC brush: brass wire

Sealing ring: elastomer

O-ring: elastomer

Protection rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112681 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.