

**INDUSTRIAL COMPONENT DATA**

# 53112691 SKINTOP CLICK-R 25 RAL 7035 LGY LAPP

## SKINTOP CLICK-R 25 RAL 7035 LGY

Brand: LAPP | Manufacturer Part Number: 53112691



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | LAPP                            |
| MPN / Reference | 53112691                        |
| Catalog number  | SKINTOP CLICK-R 25 RAL 7035 LGY |
| Category        | Cable gland                     |
| Minimum order   | 25 Pcs                          |
| Document ID     | EO-E5CC491175                   |
| Generated       | 2026-08-05                      |

### Product Overview

SKINTOP CLICK-R 25 RAL 7035 LGY

SKINTOP® CLICK-R

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path      LAPP > SKINTOP cabling

### Additional Product Information

SKINTOP® CLICK-R, plastic cable gland with time-saving CLICK system, simple, free assembly, with reducing seal insert. The most innovative cable insertion system in the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - finished. The result: fixed, centred, strain-relieved fitting and maximum protection class in a few seconds.

**Benefits**

Fewer parts, counter nut no longer needed

Save up to 70% of the time with the innovative CLICK system

Simple, free assembly in any position

Vibration protection

No thread required

Application range

With reducing seal insert, to seal cables with smaller outer diameters

Norm references / Approvals

UL File Nr. E79903

Included

Included: disassembly tool

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Colour delivered

Silver grey (RAL 7001)

Light grey (RAL 7035)

Black (RAL 9005), UV-resistant

Material

Body: special polyamide

Seal: special elastomer

Protection rating

IP 68 - 4 bar (M12)

IP 68 - 5 bar (M16 - M25)

IP 68 - 1 bar (M32)

Temperature range

Dynamic: -20°C to +100°C

Fixed: -40°C to +100°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112691 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.