

INDUSTRIAL COMPONENT DATA

53112730 SKINTOP MS-M 25x1,5 ATEX LAPP SKINTOP MS-M 25x1,5 ATEX

Brand: LAPP | Manufacturer Part Number: 53112730



Manufacturer	LAPP
MPN / Reference	53112730
Catalog number	SKINTOP MS-M 25x1,5 ATEX
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-127312E75B
Generated	2026-08-04

Product Overview

SKINTOP MS-M 25x1,5 ATEX

SKINTOP® MS-M ATEX

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® MS-M ATEX, anti-static brass cable gland with cold impact resistance and maximum reliability, explosion-proof

Benefits

Cold impact resistance

High strain relief

Wide, variable clamping ranges

Maximum reliability

Application range

Devices, machines and apparatus of enhanced safety protection type "e", dust ignition proof "t"

Equipment group II / Category 2G+1D

For mobile applications in offshore and marine industries

Chemical and petrochemical industry

Product features

SKINTOP® MS-M-XL ATEX is similar to the SKINTOP® MS-M ATEX, but has an extended connection thread for thick walls

Norm references / Approvals

UL File Nr. E79903

M 63 plus without UL approval

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to the instruction leaflet for the installation dimensions and torques

Certifications

CE 0637 Ex II 2G

Ex eb IIC Ex II 1D

Ex ta IIIC

IECEx IBE 13.0026X

Material

Body: nickel-plated brass

Insert: polyamide

Sealing: CR

O-ring: NBR

Tests

DIN EN 60079-0

DIN EN 60079-7

DIN EN 60079-31

Protection rating

IP 68 - 10 bar

IP 66

NEMA Type 1, 4x, 6, 12

Temperature range

-30°C to +90°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112730 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.