

INDUSTRIAL COMPONENT DATA

53112907 SKINTOP CLICK BS 20 RAL 7001 SGY LAPP

SKINTOP CLICK BS 20 RAL 7001 SGY

Brand: LAPP | Manufacturer Part Number: 53112907



Manufacturer	LAPP
MPN / Reference	53112907
Catalog number	SKINTOP CLICK BS 20 RAL 7001 SGY
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-571ABDC255
Generated	2026-08-06

Product Overview

SKINTOP CLICK BS 20 RAL 7001 SGY
SKINTOP® CLICK BS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® CLICK BS, bending protection with innovative CLICK system to protect flexible cables, no thread required, no counter nut

The most innovative cable insertion system in the market for a fast and highly flexible assembly. Simply click in - turn to the left - turn to the right - finished. The result: fixed, centred, strain-relieved fitting and maximum protection class in a few seconds.

Benefits

Reliable bending protection for cable conservation and functional reliability

Save up to 70% of the time with the innovative CLICK system

No thread required

To protect flexible cables

Fewer parts, counter nut no longer needed

Application range

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Robotics industry
Moving machine parts
Apparatus construction
Light and sound applications
Norm references / Approvals
UL File Nr. E79903
Included
Included: disassembly tool
Classification ETIM 5
ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland
Classification ETIM 6
ETIM 6.0 Class-ID: EC000441
ETIM 6.0 Class-Description: Cable screw gland
Colour delivered
Silver grey (RAL 7001)
Light grey (RAL 7035)
Black (RAL 9005), UV-resistant
Material
Body: special polyamide
Seal: special elastomer
Protection rating
IP 68 - 4 bar (M12)
IP 68 - 5 bar (M16 - M25)
IP 68 - 1 bar (M32)
Temperature range
-20°C to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53112907 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.