

INDUSTRIAL COMPONENT DATA

53806726 SKINTOP INOX SC M 25 LAPP SKINTOP INOX SC M 25

Brand: LAPP | Manufacturer Part Number: 53806726



Manufacturer	LAPP
MPN / Reference	53806726
Catalog number	SKINTOP INOX SC M 25
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-308FEBBAF4
Generated	2026-08-04

Product Overview

SKINTOP INOX SC M 25

SKINTOP® INOX SC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

Benefits

Smooth surfaces - no edges

Compact design

Wide, variable clamping ranges

Low-resistance screen contact, optimum EMC protection

Highly conductive, flexible EMC contact for clamping various screen diameters

Application range

For EMC-compliant earthing of the copper braiding

Pharmaceutical industry

Food industry (product-free zone, splash zone)

Onshore and offshore applications

Bottling plants and breweries

Norm references / Approvals

DIN EN ISO 14159

Security of machinery - Hygienic requirements for the design of machinery

DIN EN 1672-2

Guideline for the design of machinery

ECOLAB®

Industry standard in the field of professional cleaning and disinfection in the food and beverage industry

NSF/ANSI 169

Hygienic design for machinery and components

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

SKINDICHT® SM-PE-M counter nut should be used to ensure optimum contact with painted, anodised or powder-coated housings

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to the instruction leaflet for the installation dimensions and torques

Material

Body: stainless steel V4A

(1.4404 / 316L)

Insert: polyamide

Sealing: silicone

O-Ring: silicone

Halogen-free

Protection rating

IP 68 - 10 bar (M12 - M20)

IP 68 - 5 bar (M25 - M50)

IP 69

NEMA Type 1, 2, 4x, 6, 12

Tempera...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53806726 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.