

INDUSTRIAL COMPONENT DATA

53806751 SKINTOP INOX-R M20x1,5 LAPP SKINTOP INOX-R M20x1,5

Brand: LAPP | Manufacturer Part Number: 53806751



Manufacturer	LAPP
MPN / Reference	53806751
Catalog number	SKINTOP INOX-R M20x1,5
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-90F9702BB4
Generated	2026-08-05

Product Overview

SKINTOP INOX-R M20x1,5
SKINTOP® INOX / SKINTOP® INOX-R

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	LAPP > SKINTOP cabling
--------------	------------------------

Additional Product Information

SKINTOP® INOX / SKINTOP® INOX-R, corrosion-resistant stainless steel cable gland with smooth surfaces, compact design, sea water-resistant

Stainless steel version with compact design

For use in the splash zone in the food production

Benefits

Corrosion-resistant

Sea water-resistant

Smooth surfaces - no edges

Compact design

Wide, variable clamping ranges

Application range

Onshore and offshore applications

Bottling plants and breweries

Food industry (product-free zone, splash zone)

Norm references / Approvals

ECOLAB®

Industry standard in the field of professional cleaning and disinfection in the food and beverage industry

DIN EN 1672-2

Guideline for the design of machinery

DIN EN ISO 14159

Security of machinery - Hygienic requirements for the design of machinery

NSF/ANSI 169

Hygienic design for machinery and components

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Material

Body: stainless steel V4A

(1.4404 / 316L)

Insert: polyamide

Sealing: silicone

O-Ring: silicone

Halogen-free

Protection rating

IP 68 - 10 bar (M12 - M20)

IP 68 - 5 bar (M25 - M50)

IP 69

NEMA Type 1, 2, 4x, 6, 12

Temperature range

-40°C to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53806751 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.