

INDUSTRIAL COMPONENT DATA

53806761 SKINTOP BS-M METALL M20x1,5 LAPP SKINTOP BS-M METALL M20x1,5

Brand: LAPP | Manufacturer Part Number: 53806761



Manufacturer	LAPP
MPN / Reference	53806761
Catalog number	SKINTOP BS-M METALL M20x1,5
Category	Cable gland
Minimum order	25 Pcs
Document ID	EO-4A77FF7BEF
Generated	2026-08-04

Product Overview

SKINTOP BS-M METALL M20x1,5

SKINTOP® BS-M METAL / SKINTOP® BSR-M METAL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > SKINTOP cabling

Additional Product Information

SKINTOP® BS-M METAL / SKINTOP® BSR-M METAL, durable cable gland with permanent bending protection under high mechanical stress

Permanent bending protection under high mechanical stress

Benefits

High mechanical stability

Long service life

Optimum strain relief

Wide, variable clamping ranges

Maximum reliability

Application range

In areas where mechanical stability are critical

Portable equipment

Building sites

Machine and equipment manufacturing

Typical fields of application

- Steel and glass works
- Cement and ceramic works
- Foundries
- Shipbuilding industry
- Furnace construction

Norm references / Approvals

Cables for electrical appliances and machinery that are moved under normal use must be protected against excessive bending as required in accordance with VDE 0700-1

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Note

M32 x 1,5 on request

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to Appendix T21 for the installation dimensions and torques

Material

Body: nickel-plated brass

Insert: polyamide

Sealing: CR

O-ring: NBR

Spiral - springs made of stainless steel

Protection rating

IP 68 - 10 bar

IP 69

Temperature range

Dynamic: -25°C up to +100°C

Fixed: -30°C up to +100°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 53806761 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.