

## INDUSTRIAL COMPONENT DATA

# 54115255 SKINTOP KR-M 40x1,5 ATEX plus BK LAPP

## SKINTOP KR-M 40x1,5 ATEX plus BK

Brand: LAPP | Manufacturer Part Number: 54115255



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | LAPP                             |
| MPN / Reference | 54115255                         |
| Catalog number  | SKINTOP KR-M 40x1,5 ATEX plus BK |
| Category        | Cable gland                      |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-D68707766B                    |
| Generated       | 2026-08-05                       |

### Product Overview

SKINTOP KR-M 40x1,5 ATEX plus BK

SKINTOP® KR-M ATEX plus

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path LAPP &gt; SKINTOP cabling

### Additional Product Information

SKINTOP® KR-M ATEX plus, metric plastic cable gland with high degree of protection and reducing seal insert, explosion proof

## Benefits

High degree of protection

Cold impact resistance

High strain relief

Wide, variable clamping ranges

Permanent vibration protection

Application range

With reducing seal insert, to seal cables with smaller outer diameters

Product Make-up

Metric connection thread acc. to DIN EN 60423

Basis for technical information DIN IEC 62444

Classification ETIM 5

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

Caution

Refer to the instruction leaflet for the installation dimensions and torques

Certifications

CE 0637 Ex II 2G

Ex eb IIC Ex II 1D

Ex ta IIIC

IECEX IBE 13.0027X

Colour delivered

Black (RAL 9005), UV-resistant

Material

Body: special polyamide

Seal: special elastomer

O-ring: CR

Tests

DIN EN 60079-0

DIN EN 60079-7

DIN EN 60079-31

Protection rating

IP 68 - 10 bar

Temperature range

-20°C to +80°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 54115255 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.