

**INDUSTRIAL COMPONENT DATA**

# 55500810 SILVYN KCLICK-GPZ-M 16x1,5 GY LAPP SILVYN KCLICK-GPZ-M 16x1,5 GY

Brand: LAPP | Manufacturer Part Number: 55500810



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | LAPP                                         |
| MPN / Reference | 55500810                                     |
| Catalog number  | SILVYN KCLICK-GPZ-M 16x1,5 GY                |
| Category        | Screw connection for corrugated plastic hose |
| Minimum order   | 20 Pcs                                       |
| Document ID     | EO-67FE9E5D42                                |
| Generated       | 2026-08-05                                   |

## Product Overview

SILVYN KCLICK-GPZ-M 16x1,5 GY

SILVYN® KCLICK GPZ-M

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SILVYN cabling

## Additional Product Information

SILVYN® KCLICK GPZ-M - metric conduit fitting with integrated cable strain relief for SILVYN® RILL

Benefits

Fast assembly

Easy to disassemble

Additional cable strain relief

Additional cable sealing

Application range

In combination with protective conduit:

SILVYN® RILL PA 6

SILVYN® RILL PA 12

Robot-building

Used in areas where cables and wires need to be provided with strain relief and additional sealing

Norm references / Approvals

UL FILENUMBER E308201

Product Make-up

Metric connection thread

Cable gland

Body with inner sealing

Upper part with snap-in sleeve

Note

PG threaded versions are to be found in the online catalogue

Classification ETIM 5

ETIM 5.0 Class-ID: EC001176

ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001176

ETIM 6.0 Class-Description: Screw connection for corrugated plastic hose

Colour delivered

Grey (RAL 7031)

Black (RAL 9011), UV-resistant

Material

PA6

Protection rating

IP 68

IP 69

Temperature range

-40 °C to +115 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 55500810 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.