

INDUSTRIAL COMPONENT DATA

55502003 SILVYN LGS-2-M 16x1,5/1 LAPP SILVYN LGS-2-M 16x1,5/1

Brand: LAPP | Manufacturer Part Number: 55502003

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	LAPP
MPN / Reference	55502003
Catalog number	SILVYN LGS-2-M 16x1,5/1
Category	Screw connection for protective metallic hose
Minimum order	10 Pcs
Document ID	EO-F8599B413E
Generated	2026-08-04

Product Overview

SILVYN LGS-2-M 16x1,5/1

SILVYN® LGS-2-M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > SILVYN cabling

Additional Product Information

SILVYN® LGS-2-M is a swivelling nickel-plated brass conduit fitting for installation with torsional movements

Benefits

For rotating applications

High tensile strength

Space-saving

Application range

In combination with protective conduit:

SILVYN® LCC-2

SILVYN® LCCH-2

Applications with high mechanical stress

Outdoors

Product Make-up

Metric connection thread

Hexagonal collar with torsion element

Cap nut

Classification ETIM 5

ETIM 5.0 Class-ID: EC001180

ETIM 5.0 Class-Description: Screw connection for protective metallic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001180

ETIM 6.0 Class-Description: Screw connection for protective metallic hose

Norm references / Approvals

Material

Nickel-plated brass

Protection rating

IP 54

Temperature range

-50°C to +300°C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 55502003 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.