

**INDUSTRIAL COMPONENT DATA**

# 55502444 SILVYN MPC M20.2 GY LAPP SILVYN MPC M20.2 GY

Brand: LAPP | Manufacturer Part Number: 55502444



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | LAPP                                         |
| MPN / Reference | 55502444                                     |
| Catalog number  | SILVYN MPC M20.2 GY                          |
| Category        | Screw connection for protective plastic hose |
| Minimum order   | 10 Pcs                                       |
| Document ID     | EO-6F030B29B1                                |
| Generated       | 2026-08-02                                   |

## Product Overview

SILVYN MPC M20.2 GY

SILVYN® MPC-M

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | LAPP > SILVYN cabling |
|--------------|-----------------------|

## Additional Product Information

SILVYN® MPC-M - conduit fitting for use with SILVYN® EL/ELU/ELO/ELT

Benefits

All-purpose

Fast and easy assembly

Application range

In combination with protective conduit:

SILVYN® EL/ELU/ELO/ELT/ELR (helically formed and smooth conduits)

Product features

Dust protection

Moisture-protection

Ensures high tensile strength and mechanical protection

Norm references / Approvals

UL FILENUMBER E308201

Product Make-up

Metric connection thread

Hexagonal collar with integrated conduit connection

Note

PG threaded versions are to be found in the online catalogue

Classification ETIM 5

ETIM 5.0 Class-ID: EC001178

ETIM 5.0 Class-Description: Screw connection for protective plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001178

ETIM 6.0 Class-Description: Screw connection for protective plastic hose

Certifications

IEC EN 61386-23

Colour delivered

Black (RAL 9005), UV-resistant

Grey, RAL 7001

Material

PA66

Halogen-free

Protection rating

IP 65 with helically formed conduits

IP 67 + IP 68 (2bar) with smooth conduits

Temperature range

-40°C to +120°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 55502444 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.