

**INDUSTRIAL COMPONENT DATA**

# 55502621 SILVYN US-M 10X1 AS-P LAPP SILVYN US-M 10X1 AS-P

Brand: LAPP | Manufacturer Part Number: 55502621

PRODUCT IMAGE\nNOT  
AVAILABLE

|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | LAPP                                          |
| MPN / Reference | 55502621                                      |
| Catalog number  | SILVYN US-M 10X1 AS-P                         |
| Category        | Screw connection for protective metallic hose |
| Minimum order   | 50 Pcs                                        |
| Document ID     | EO-7280F6DAED                                 |
| Generated       | 2026-08-06                                    |

## Product Overview

SILVYN US-M 10X1 AS-P

SILVYN® US-M

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path LAPP > SILVYN cabling

## Additional Product Information

SILVYN® US-M is a nickel-plated brass conduit fitting that offers IP40 / IP54 / IP66 protection degree depending on the used conduit

Benefits

High tensile strength

Space-saving

Vibration protection

All-purpose

Fast and easy assembly

Application range

In combination with protective conduit:

SILVYN®AS/AS-P/EDU-AS/EMC AS-CU

Mechanical engineering

Plant engineering

Product features

Compact design

Product Make-up

Metric connection thread

Hexagonal collar

Threaded sleeve

Sealing element

Cap nut

Note

PG threaded versions are to be found in the online catalogue

Classification ETIM 5

ETIM 5.0 Class-ID: EC001180

ETIM 5.0 Class-Description: Screw connection for protective metallic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001180

ETIM 6.0 Class-Description: Screw connection for protective metallic hose

Material

Body: nickel-plated brass

Sealing ring: TPE

Protection rating

IP 40 (with SILVYN® AS, EDU-AS and EMC AS-CU)

IP 65 (with SILVYN® AS-P)

Temperature range

-40°C to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 55502621 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.