

**INDUSTRIAL COMPONENT DATA**

# 55502692 SILVYN US PG 16 FPS-EDU LAPP SILVYN US PG 16 FPS-EDU

Brand: LAPP | Manufacturer Part Number: 55502692



|                 |                                               |
|-----------------|-----------------------------------------------|
| Manufacturer    | LAPP                                          |
| MPN / Reference | 55502692                                      |
| Catalog number  | SILVYN US PG 16 FPS-EDU                       |
| Category        | Screw connection for protective metallic hose |
| Minimum order   | 50 Pcs                                        |
| Document ID     | EO-35E0E84C1A                                 |
| Generated       | 2026-08-03                                    |

## Product Overview

SILVYN US PG 16 FPS-EDU

SILVYN® US FPS-EDU

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | LAPP > SILVYN cabling |
|--------------|-----------------------|

## Additional Product Information

SILVYN® US is a PG threaded nickel-plated brass conduit fitting that offers IP40 / IP54 / IP66 protection degree depending on the used conduit

Benefits

High tensile strength

Space-saving

Vibration protection

All-purpose

Fast and easy assembly

Application range

In combination with protective conduit:

SILVYN®FPS-EDU

Mechanical engineering

Plant engineering

Product features

Compact design  
Product Make-up  
PG connection thread  
Hexagonal collar  
Threaded sleeve  
Sealing element  
Cap nut  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC001180  
ETIM 5.0 Class-Description: Screw connection for protective metallic hose  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC001180  
ETIM 6.0 Class-Description: Screw connection for protective metallic hose  
Material  
Body: nickel-plated brass  
Sealing ring: TPE  
Protection rating  
IP 54 (with SILVYN® FPS-EDU)  
Temperature range  
-40°C to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 55502692 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.