

**INDUSTRIAL COMPONENT DATA**

# 61742407 PROTECT 12.7/6.4 BK LAPP Shrink tube PROTECT 12.7/6.4 BK

Brand: LAPP | Manufacturer Part Number: 61742407



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | LAPP                |
| MPN / Reference | 61742407            |
| Catalog number  | PROTECT 12.7/6.4 BK |
| Category        | Shrink tubing       |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-7891B0E956       |
| Generated       | 2026-07-29          |

## Product Overview

Shrink tube PROTECT 12.7/6.4 BK

Shrink tube PROTECT

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                    |
|--------------|--------------------|
| Catalog path | LAPP > Accessories |
|--------------|--------------------|

## Additional Product Information

The shrink tube is particularly interesting for the North American market due to various approvals such as CSA and UR. The shrinking ratio is 2:1.

Thin walled

Benefits

Flexible

Excellent physical and mechanical properties

Approved for the use in North America and Canada

Application range

Insulation, protection and cable bundling

Green-yellow shrink tube: For identifying and marking earthing connectors and cables

Product features

Flame-retardant (except colour: clear)

Silicone-free

UV-resistant (only colour: black)

Norm references / Approvals

UL 224 approval (except colour: transparent)

UL file no.: E476215 (except colour: transparent)

Note

Not resistant against engine oils

Included

Plastic bag with 1.22 m units

Classification ETIM 5

ETIM 5.0 Class-ID: EC000217

ETIM 5.0 Class-Description: Heat-shrink tubing

Classification ETIM 6

ETIM 6.0 Class-ID: EC000217

ETIM 6.0 Class-Description: Shrink tubing

On request

Other colours are available upon request

Note

Thin walled

Dielectric strength: 20 kV/mm

Info

Shrinking ratio: 2:1

Colour delivered

Black

Transparent

Green-yellow

Material

Cross-linked polyolefin

Temperature range

-55°C to +135°C

Shrinking temperature: +90°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61742407 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.