

**INDUSTRIAL COMPONENT DATA**

# 61742420 PROTECT 12.7/6.4GN/YE LAPP Shrink tube

## PROTECT 12.7/6.4GN/YE

Brand: LAPP | Manufacturer Part Number: 61742420



|                 |                       |
|-----------------|-----------------------|
| Manufacturer    | LAPP                  |
| MPN / Reference | 61742420              |
| Catalog number  | PROTECT 12.7/6.4GN/YE |
| Category        | Shrink tubing         |
| Minimum order   | 1 Pcs                 |
| Document ID     | EO-C749CA046C         |
| Generated       | 2026-08-04            |

### Product Overview

Shrink tube PROTECT 12.7/6.4GN/YE

Shrink tube PROTECT

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                    |
|--------------|--------------------|
| Catalog path | LAPP > Accessories |
|--------------|--------------------|

### Additional Product Information

Benefits

Flexible

Excellent physical and mechanical properties

Approved for the use in North America and Canada

Application range

Insulation, protection and cable bundling

Green-yellow shrink tube: For identifying and marking earthing connectors and cables

Product features

Flame-retardant (except colour: clear)

Silicone-free

UV-resistant (only colour: black)

Norm references / Approvals

UL 224 approval (except colour: transparent)

UL file no.: E476215 (except colour: transparent)

**Note**

Not resistant against engine oils

**Included**

Plastic bag with 1.22 m units

**Classification ETIM 5**

ETIM 5.0 Class-ID: EC000217

ETIM 5.0 Class-Description: Heat-shrink tubing

**Classification ETIM 6**

ETIM 6.0 Class-ID: EC000217

ETIM 6.0 Class-Description: Shrink tubing

**On request**

Other colours are available upon request

**Note**

Thin walled

Dielectric strength: 20 kV/mm

**Info**

Shrinking ratio: 2:1

Colour delivered

Black

Transparent

Green-yellow

**Material**

Cross-linked polyolefin

**Temperature range**

-55°C to +135°C

Shrinking temperature: +90°C

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send LAPP / 61742420 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.