

**INDUSTRIAL COMPONENT DATA**

# 61742424 PROTECT BOX 1.6/0.8 BK LAPP Shrink tube

## PROTECT Box 1.6/0.8 BK

Brand: LAPP | Manufacturer Part Number: 61742424



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | LAPP                   |
| MPN / Reference | 61742424               |
| Catalog number  | PROTECT BOX 1.6/0.8 BK |
| Category        | Shrink tubing          |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-76ADB12F2B          |
| Generated       | 2026-08-03             |

### Product Overview

Shrink tube PROTECT Box 1.6/0.8 BK

Shrink tube PROTECT Box

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                    |
|--------------|--------------------|
| Catalog path | LAPP > Accessories |
|--------------|--------------------|

### Additional Product Information

The shrinkable plastic conduit in an handy box is especially suitable for small-scale consumers.

Thin walled

Benefits

Flexible

Excellent physical and mechanical properties

Approved for the use in North America and Canada

Application range

Insulation, protection and cable bundling

Green-yellow shrink tube: For identifying and marking earthing connectors and cables

Product features

Flame-retardant (except colour: clear)

Silicone-free

UV-resistant (only colour: black)

Norm references / Approvals

UL 224 approval (except colour: transparent)

UL file no.: E476215 (except colour: transparent)

Note

Not resistant against engine oils

Included

Stackable boxes for easy storage

Classification ETIM 5

ETIM 5.0 Class-ID: EC000217

ETIM 5.0 Class-Description: Heat-shrink tubing

Classification ETIM 6

ETIM 6.0 Class-ID: EC000217

ETIM 6.0 Class-Description: Shrink tubing

On request

Other colours are available upon request

Note

Thin walled

Dielectric strength: 20 kV/mm

Info

Shrinking ratio: 2:1

Colour delivered

Black

Transparent

Green-yellow

Material

Cross-linked polyolefin

Temperature range

-55°C to +135°C

Shrinking temperature: +90°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61742424 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.