

**INDUSTRIAL COMPONENT DATA**

# 61746940 SILVYN RILL PA6 13 / 10x13 GY LAPP SILVYN RILL PA6 13 / 10x13 GY

Brand: LAPP | Manufacturer Part Number: 61746940



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LAPP                          |
| MPN / Reference | 61746940                      |
| Catalog number  | SILVYN RILL PA6 13 / 10x13 GY |
| Category        | Corrugated plastic hose       |
| Minimum order   | 50 m.                         |
| Document ID     | EO-C5B8F34D4C                 |
| Generated       | 2026-08-05                    |

## Product Overview

SILVYN RILL PA6 13 / 10x13 GY

SILVYN® RILL PA 6

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | LAPP > SILVYN cabling |
|--------------|-----------------------|

## Additional Product Information

SILVYN® RILL PA6 is the classic parallel corrugated conduit that offers best protection due to its structure and versatile accessories

Maximum safety in the event of a fire

Benefits

Dimensionally stable

Flexible

High flame-retardance and self-extinguishing in accordance with UL 94V-0

Crush-resistant

Lightweight

Application range

Mechanical engineering

Public utilities

Railway applications / vehicle construction

Moving applications

Outdoor application (in black)

Product features

Halogen and cadmium-free

Abrasion-resistant

High resistance to oil, petrol, acids and other chemicals

Norm references / Approvals

UL FILENUMBER E308201

Product Make-up

Fine-profile corrugated polyamide 6 conduit

Note

UV and weather-resistant in black

Classification ETIM 5

ETIM 5.0 Class-ID: EC001175

ETIM 5.0 Class-Description: Corrugated plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001175

ETIM 6.0 Class-Description: Corrugated plastic hose

Certifications

IEC EN 61386-23

UL File No. E308201

DNV, Lloyd's Register

EN 45545-2 (HL-3)

Colour delivered

Grey (RAL 7031)

Black (RAL 9011), UV-resistant

Material

PA 6

Silicone-free

Halogen-free

Fire behaviour according to UL 94V-0

Temperature range

-40°C to +115°C

short-term +150°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61746940 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.