

**INDUSTRIAL COMPONENT DATA**

# 61754045 SILVYN FPAS PA6 28 / 22,8x28,5 BK LAPP SILVYN FPAS PA6 28 / 22,8x28,5 BK

Brand: LAPP | Manufacturer Part Number: 61754045



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | LAPP                              |
| MPN / Reference | 61754045                          |
| Catalog number  | SILVYN FPAS PA6 28 / 22,8x28,5 BK |
| Category        | Corrugated plastic hose           |
| Minimum order   | 50 m.                             |
| Document ID     | EO-1FA1804722                     |
| Generated       | 2026-08-05                        |

## Product Overview

SILVYN FPAS PA6 28 / 22,8x28,5 BK

SILVYN® FPAS

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SILVYN cabling

## Additional Product Information

SILVYN® FPAS is a parallel corrugated conduit, offers best cable protection together with its versatile accessories

Benefits

Dimensionally stable

Flexible

Flame-retardant and self-extinguishing according to UL 94V-2

High crush-resistance

Impact-resistant

Application range

Mechanical engineering

Plant engineering

Railway applications / vehicle construction

Moving applications

For indoor and outdoor use

Product features

Halogen and cadmium-free  
Abrasion-resistant  
High resistance to oil, petrol, acids and other chemicals  
Inherent Low Fire Hazard  
Norm references / Approvals  
UL FILENUMBER E308201  
Product Make-up  
Fine-profile corrugated polyamide 6 conduit  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC001175  
ETIM 5.0 Class-Description: Corrugated plastic hose  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC001175  
ETIM 6.0 Class-Description: Corrugated plastic hose  
Certifications  
IEC EN 61386-23  
On request  
Available in PA 12  
Colour delivered  
Grey (RAL 7031)  
Black (RAL 9005), UV-resistant  
Material  
PA 6  
Halogen-free  
Fire behaviour according to UL94 V-2  
Temperature range  
-40°C to +120°C static  
-20°C to +100°C dynamic

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61754045 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.