

**INDUSTRIAL COMPONENT DATA**

# 61800880 SILVYN KCLICK PG 11 GY LAPP SILVYN KCLICK PG 11 GY

Brand: LAPP | Manufacturer Part Number: 61800880



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | LAPP                                         |
| MPN / Reference | 61800880                                     |
| Catalog number  | SILVYN KCLICK PG 11 GY                       |
| Category        | Screw connection for corrugated plastic hose |
| Minimum order   | 50 Pcs                                       |
| Document ID     | EO-6F17827AA6                                |
| Generated       | 2026-08-03                                   |

## Product Overview

SILVYN KCLICK PG 11 GY  
SILVYN® KCLICK PG

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | LAPP > SILVYN cabling |
|--------------|-----------------------|

## Additional Product Information

SILVYN® KCLICK PG - PG threaded conduit fitting for SILVYN® RILL

Benefits

Fast assembly

Easy to disassemble

High-tensile

High sealing performance

Can be rotated

Application range

In combination with protective conduit:

SILVYN® RILL PA 6

SILVYN® RILL PA 12

Robot-building

Rotating applications

Norm references / Approvals

UL FILENUMBER E308201

Product Make-up

PG connection thread

Body with inner sealing

Upper part with snap-in sleeve

Classification ETIM 5

ETIM 5.0 Class-ID: EC001176

ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001176

ETIM 6.0 Class-Description: Screw connection for corrugated plastic hose

Colour delivered

Grey (RAL 7031)

Black (RAL 9011), UV-resistant

Material

PA6

Halogen-free

Protection rating

IP 68

IP 69

Temperature range

-40 °C to +115 °C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61800880 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.