

## INDUSTRIAL COMPONENT DATA

## 61803040 KRF/16-10 LAPP TUBE CABLE LUGS KRF/16-10

Brand: LAPP | Manufacturer Part Number: 61803040



|                 |                                         |
|-----------------|-----------------------------------------|
| Manufacturer    | LAPP                                    |
| MPN / Reference | 61803040                                |
| Catalog number  | KRF/16-10                               |
| Category        | Tubular cable lug for copper conductors |
| Minimum order   | 100 Pcs                                 |
| Document ID     | EO-0B3E4861A1                           |
| Generated       | 2026-08-04                              |

## Product Overview

TUBE CABLE LUGS KRF/16-10

Tube cable lugs KR/ KRT/ KRF

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LAPP &gt; Connection engineering

## Additional Product Information

Tube cable lugs KR/KRT/KRF with inspection hole

Benefits

With inspection hole (starting from 4 mm<sup>2</sup>)

High-quality electrolytic copper ensures a good crimping quality

Application range

KR: For fine and multi-wire copper conductors (class 2 and 5) with a cross-sectional range of 0.75 -10.00 mm<sup>2</sup>KRT: For multi-wire copper conductors (class 2) with a cross-sectional range of 10 - 1000 mm<sup>2</sup>KRF: For fine wire copper conductors (class 2, 5 and 6) with a cross-sectional range of 16 - 800 mm<sup>2</sup>

Mainly for connection to rails and to copper connectors

Max. 48 kV

Norm references / Approvals

UL file number: E205350 (see table)

In combination with recommended crimp tool fulfill requirements of EN-IEC 61238:1, BS 4579:1 and VDE 0220:1

Classification ETIM 5

ETIM 5.0 Class-ID: EC001051

ETIM 5.0 Class-Description: Tube cable lug for copper conductors

Classification ETIM 6

ETIM 6.0 Class-ID: EC001051

ETIM 6.0 Class-Description: Tube cable lug for copper conductors

Material

Tinned electrolyte copper (Cu/Sn4 , tin surface of 4μ)

Temperature range

Temperature range up to +90°C

Working temperature: 110°C, max. +140°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61803040 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.