

**INDUSTRIAL COMPONENT DATA**

# 61804796 SILVYN LCCH-2 25/21,1x26 BK LAPP SILVYN LCCH-2 25/21,1x26 BK

Brand: LAPP | Manufacturer Part Number: 61804796



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | LAPP                        |
| MPN / Reference | 61804796                    |
| Catalog number  | SILVYN LCCH-2 25/21,1x26 BK |
| Category        | Protective metallic hose    |
| Minimum order   | 25 m.                       |
| Document ID     | EO-CA57A596FA               |
| Generated       | 2026-08-05                  |

## Product Overview

SILVYN LCCH-2 25/21,1x26 BK

SILVYN® LCCH-2

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | LAPP > SILVYN cabling |
|--------------|-----------------------|

## Additional Product Information

SILVYN® LCCH-2 is a metal conduit with one-hook profile, offers good flexibility and a liquidtight halogen-free PVC jacket  
Halogen-free

**Benefits**

High flame-retardance and self-extinguishing in accordance with UL 94V-0

Protects against liquids

High crush-resistance

Suitable for outdoor use and direct burial

High mechanical resistance

**Application range**

Public utilities

Mechanical engineering

Used in areas where liquids are present

Applications with high mechanical stress

Outdoors

**Product features**

Halogen-free

low smoke

Low toxicity

**Product Make-up**

Helically-wound metal protective conduit with interlocked profile

Plastic outer sheath

**Classification ETIM 5**

ETIM 5.0 Class-ID: EC001179

ETIM 5.0 Class-Description: Protective metallic hose

**Classification ETIM 6**

ETIM 6.0 Class-ID: EC001179

ETIM 6.0 Class-Description: Protective metallic hose

**Norm references / Approvals**

IEC EN 61386-23

**Colour delivered**

Black (RAL 9005), UV-resistant

**Material**

Inner conduit: steel, galvanised

Outer sheath: plastic, halogen-free

Fire behaviour according to UL 94V-0

**Temperature range**

-25°C to +90°C

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send LAPP / 61804796 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.