

**INDUSTRIAL COMPONENT DATA**

# 61806660 SILVYN SPLIT PA6 37 / 31,0x41,4 BK LAPP SILVYN SPLIT PA6 37 / 32,5X41,9 BK 25M

Brand: LAPP | Manufacturer Part Number: 61806660



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 61806660                           |
| Catalog number  | SILVYN SPLIT PA6 37 / 31,0x41,4 BK |
| Category        | Corrugated plastic hose            |
| Minimum order   | 25 m.                              |
| Document ID     | EO-D04B41A3F7                      |
| Generated       | 2026-08-01                         |

## Product Overview

SILVYN SPLIT PA6 37 / 32,5X41,9 BK 25M

SILVYN® SPLIT

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SILVYN cabling

## Additional Product Information

SILVYN® SPLIT is a parallel corrugated, divisible conduit that is qualified for subsequent installation

Subsequent cable protection

Benefits

Dimensionally stable

Flexible

Crush-resistant

Low rodent-protection

Fast and easy assembly

Application range

Vehicle construction

Shipbuilding

Mechanical engineering

Electrical industry

Used in areas where cables and wires need to be protected after assembly

**Product features**

Halogen-free (PA6)

Abrasion-resistant

High resistance to oil, petrol, acids and other chemicals

Very good UV- and Weathering performance (SILVYN® SPLIT PP UV)

**Product Make-up**

Divisible corrugated conduit

Classification ETIM 5

ETIM 5.0 Class-ID: EC001175

ETIM 5.0 Class-Description: Corrugated plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001175

ETIM 6.0 Class-Description: Corrugated plastic hose

On request

Polyamide 12 version (highly flexible)

ETFE version (high-temperature resistant up to +200°C)

Colour delivered

Black (RAL 9005), UV-resistant

**Material**

Polyamide 6 (PA6)

Polypropylene (PP)

**Protection rating**

IP 43 with SILVYN® SPLIT COV

**Temperature range**

PA6 : -40°C to +120°C

PP : -40°C to +135°C

PP UV: -40°C to +105°C

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**Send LAPP / 61806660 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.