

**INDUSTRIAL COMPONENT DATA**

# 61815115 SILVYN RILL PA12 13 / 10x13 BK LAPP SILVYN RILL PA12 13 / 10x13 BK

Brand: LAPP | Manufacturer Part Number: 61815115



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | LAPP                           |
| MPN / Reference | 61815115                       |
| Catalog number  | SILVYN RILL PA12 13 / 10x13 BK |
| Category        | Corrugated plastic hose        |
| Minimum order   | 50 m.                          |
| Document ID     | EO-54A1B887ED                  |
| Generated       | 2026-08-04                     |

## Product Overview

SILVYN RILL PA12 13 / 10x13 BK

SILVYN® RILL PA 12

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SILVYN cabling

## Additional Product Information

SILVYN® RILL PA12 is the classic parallel corrugated conduit that offers best protection due to its structure and versatile accessories

Designed for continous movement

Benefits

Dimensionally stable

Highly flexible at cold temperatures

Flame-retardant and self-extinguishing according to UL 94V-2

Crush-resistant

Highly flexible

Application range

Mechanical engineering

In drag chains (SILVYN® CHAIN)

Building Automation

Robot-building

Outdoor application (in black)

Product features

Halogen and cadmium-free

Abrasion-resistant

High resistance to oil, petrol, acids and other chemicals

Norm references / Approvals

UL FILENUMBER E308201

Product Make-up

Fine-profile corrugated polyamide 12 conduit

Note

UV and weather-resistant in black

Classification ETIM 5

ETIM 5.0 Class-ID: EC001175

ETIM 5.0 Class-Description: Corrugated plastic hose

Classification ETIM 6

ETIM 6.0 Class-ID: EC001175

ETIM 6.0 Class-Description: Corrugated plastic hose

Certifications

IEC EN 61386-23

UL File No. E308201

DNV, Lloyd's Register

EN 45545-2 (HL-3)

Colour delivered

Grey (RAL 7031)

Black (RAL 9011), UV-resistant

Material

PA 12

Silicone-free

Halogen-free

Fire behaviour according to UL 94V-2

Temperature range

-50°C bis +100°C

short-term +150°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 61815115 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.