

INDUSTRIAL COMPONENT DATA

62200458 Towing trolley flat C40 35x97 LAPP Towing trolley flat C40 35x97

Brand: LAPP | Manufacturer Part Number: 62200458



Manufacturer	LAPP
MPN / Reference	62200458
Catalog number	Towing trolley flat C40 35x97
Category	Accessories/spare parts for cable carrying system
Minimum order	1 Pcs
Document ID	EO-3F1C213CD8
Generated	2026-08-01

Product Overview

Towing trolley flat C40 35x97
Energy trolley system for C-profile rails

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path LAPP > Accessories

Additional Product Information

Lapp Group offers a cable conveying system for both flat and round cables.
Calculation tool on our website (in information center: cable accessories)
proceeds
Careful cable ties prevent severe cable bending
Dustproof ball bearings (wheels) ensure smooth ride on the rails
Scope of use
Crane and transport machinery
For elevators and transport facilities
Machine building
Washing facilities
Not suitable for applications in explosive environments
Notice
Round- and flat cables are not allowed to be combined side by side or below each other
Do not mount more than three round cable clamps one underneath the other

Radius of curvature on the bracket corresponds to the value of a fixed installation

Energy trolleys with addition "b" are suitable for cables with large bending radius (see data sheet)

Delivery

Delivery length profile rail C 6 m

Product composition

The installation of a system depends on various criteria, for example: maximum cable drop (weight of the cable) and working duration.

ETS Classification 5

ETIM 5.0 Class-ID: EC002935

ETIM 5.0 Class-Description: Energy Carrier Accessory

ETIM Rating 6

ETIM 6.0 Class-ID: EC002935

ETIM 6.0 Class-Description: Energy Carrier Accessory

General

Max load capacity: C30 system: 20 kg C40 system: 32 kg

Material

Metal parts: galvanized steel Tweezers: polyamide 6

Temperature range

from -40 °C to +120 °C

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 62200458 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.