


## INDUSTRIAL COMPONENT DATA

## 63101120 L-RC 95 LAPP PANEL CONNECTORS L-RC 95

Brand: LAPP | Manufacturer Part Number: 63101120



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | LAPP                          |
| MPN / Reference | 63101120                      |
| Catalog number  | L-RC 95                       |
| Category        | Round or flat plug/receptacle |
| Minimum order   | 50 Pcs                        |
| Document ID     | EO-B40FE686EA                 |
| Generated       | 2026-07-29                    |

## Product Overview

PANEL CONNECTORS L-RC 95

Panel connectors insulated

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path LAPP &gt; Connection engineering

## Additional Product Information

Insulated panel connectors (type M, T and V), UL approved, with easy entry funnel shape

Benefits

Hard-soldered cable lug that can be pressed in any position

Thus providing the best electrical conductivity (least resistance)

No risk of bent and crushed cables

Application range

Control cabinet manufacturing

Cable assembly

Norm references / Approvals

File Number E334111, see table

Design

For higher tensile strength

For good strength and improved current conduction

Flat receptacle material in contact pressing is double-folded and hard-soldered

EASY-ENTRY funnel shape of the plastic sleeve enables simple, fast and safe insertion of the conductor

1 = push-on female terminal, type H  
2 = push-on piggyback terminal, type T  
3 = push-on male terminal, type M  
4 = push-on female terminal (fully insulated), type V  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC000516  
ETIM 5.0 Class-Description: Round plug/flat receptacle  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC000516  
ETIM 6.0 Class-Description: Round or flat plug/receptacle  
Material  
Brass tin-plated  
Polyamide, halogen-free  
Temperature range  
-20°C to +105°C  
Short-term: up to +120°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 63101120 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.