

**INDUSTRIAL COMPONENT DATA**

# 63204335 KB25-5R DIN 46234 LAPP CABLE LUGS KB25-5R DIN 46234

Brand: LAPP | Manufacturer Part Number: 63204335



|                 |                                                   |
|-----------------|---------------------------------------------------|
| Manufacturer    | LAPP                                              |
| MPN / Reference | 63204335                                          |
| Catalog number  | KB25-5R DIN 46234                                 |
| Category        | Solderless copper terminals for copper conductors |
| Minimum order   | 100 Pcs                                           |
| Document ID     | EO-51780A2861                                     |
| Generated       | 2026-08-01                                        |

## Product Overview

CABLE LUGS KB25-5R DIN 46234

Solderless cable lugs KB

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; Connection engineering

## Additional Product Information

Uninsulated cable lugs/solderless terminals according to DIN 46234, high-quality electrolytic copper for good conductivity, least resistance

**Benefits**

For first-class connection with simple operating principle

Thus providing the best electrical conductivity (least resistance)

**Application range**

For cables with category 2,5 and 6 conductors

Manufacturing of control cabinets and equipment

Trains and buses

**Norm references / Approvals**

In accordance with VG 88710

Coil form DIN 46234 (versions mit \* are not according to DIN 46234)

Classification ETIM 5

ETIM 5.0 Class-ID: EC001052

ETIM 5.0 Class-Description: Solderless copper terminals for copper conductors

Classification ETIM 6

ETIM 6.0 Class-ID: EC001052

ETIM 6.0 Class-Description: Solderless copper terminals for copper conductors

Note

s = thickness of material

Material

High-quality electrolytic copper for good conductivity

Temperature range

Temperature range up to +120°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 63204335 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.