

**INDUSTRIAL COMPONENT DATA**

# 65500485 SILVYN FLEXILOK PG 11 /13 BK LAPP SILVYN FLEXILOK PG 11 /13 BK

Brand: LAPP | Manufacturer Part Number: 65500485



|                 |                                              |
|-----------------|----------------------------------------------|
| Manufacturer    | LAPP                                         |
| MPN / Reference | 65500485                                     |
| Catalog number  | SILVYN FLEXILOK PG 11 /13 BK                 |
| Category        | Screw connection for corrugated plastic hose |
| Minimum order   | 10 Pcs                                       |
| Document ID     | EO-62BCE54C1D                                |
| Generated       | 2026-08-01                                   |

## Product Overview

SILVYN FLEXILOK PG 11 /13 BK

SILVYN® FLEXILOK PG

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      LAPP &gt; SILVYN cabling

## Additional Product Information

Benefits  
Fast assembly  
Easy to assemble  
Cost-effective conduit gland  
No loose parts  
New space-saving design  
Application range  
Mechanical engineering  
Control cabinet manufacturing  
Moving applications  
Applications with limited space  
Building Installation  
Product features  
In black colour UV-resistant and weather-proofed

One-piece slim design  
Halogen and cadmium-free  
Norm references / Approvals  
UL FILENUMBER E308201  
Product Make-up  
PG connection thread  
One-piece body  
Special clamping system  
Note  
Removeable with a screwdriver  
Classification ETIM 5  
ETIM 5.0 Class-ID: EC001176  
ETIM 5.0 Class-Description: Screw connection for corrugated plastic hose  
Classification ETIM 6  
ETIM 6.0 Class-ID: EC001176  
ETIM 6.0 Class-Description: Screw connection for corrugated plastic hose  
Norm references / Approvals  
On request  
PG 7 for FPAS 10  
PG 36 for FPAS 42  
PG 48 for FPAS 54  
Colour delivered  
Grey (RAL 7031)  
Black (RAL 9005), UV-resistant  
Material  
PA66  
Halogen-free  
Protection rating  
IP 66  
Temperature range  
-40°C to +120°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 65500485 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.