

**INDUSTRIAL COMPONENT DATA**

# 70096000 H-B 16 SDRL-BO 21 ZW. BOX MOUNT BASE LAPP

## H-B 16 SDRL-BO 21 ZW. BOX MOUNT BASE

Brand: LAPP | Manufacturer Part Number: 70096000



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | LAPP                                 |
| MPN / Reference | 70096000                             |
| Catalog number  | H-B 16 SDRL-BO 21 ZW. BOX MOUNT BASE |
| Category        | Housing for rectangular connectors   |
| Minimum order   | 5 Pcs                                |
| Document ID     | EO-2662D2042B                        |
| Generated       | 2026-08-05                           |

### Product Overview

H-B 16 SDRL-BO 21 ZW. BOX MOUNT BASE

EPIC® H-B 16 SDRL-BO

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

### Additional Product Information

The low connector housing with pivots for a double lever, 2 cable entries and a metal cap is not only ideal for use in investment construction.

Metal lid with sturdy hinge

For easy introduction of two cables

Protection rating UL50E tested

Benefits

The housing standard. Wide choice for all applications

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Surface-mount base, low version

Bolts for double lever

2 cable entries

Metal cover

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating

IP 65 (latched)

IP 40 (cover closed)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70096000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.