


**INDUSTRIAL COMPONENT DATA**

# 70135400 H-B 24 SGRH 29 ZW. BOX MOUNT BASE LAPP H-B 24 SGRH 29 ZW. BOX MOUNT BASE

Brand: LAPP | Manufacturer Part Number: 70135400



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | LAPP                               |
| MPN / Reference | 70135400                           |
| Catalog number  | H-B 24 SGRH 29 ZW. BOX MOUNT BASE  |
| Category        | Housing for rectangular connectors |
| Minimum order   | 5 Pcs                              |
| Document ID     | EO-A9802436C1                      |
| Generated       | 2026-08-06                         |

## Product Overview

H-B 24 SGRH 29 ZW. BOX MOUNT BASE

EPIC® H-B 24 SGRH

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                         |
|--------------|-------------------------|
| Catalog path | LAPP > EPIC rectangular |
|--------------|-------------------------|

## Additional Product Information

The robust metal housing with a cable entry and 2 double levers is suitable for use in investment construction applications.

Double lever version with 2 levers for increased safety

Protection rating UL50E tested

Benefits

Safe fixing with 4 screws

Casted neck for easy assembly of the cable gland

Application range

Plant engineering

Light & sound technology

Plastics industry

Product features

Surface-mount base, high version

Dual levers

1 cable entry

Classification ETIM 5

ETIM 5.0 Class-ID: EC000437

ETIM 5.0 Class-Description: Housing for industrial connectors

Classification ETIM 6

ETIM 6.0 Class-ID: EC000437

ETIM 6.0 Class-Description: Housing for industrial connectors

Material

Housing: powder-coated aluminium alloy, grey

Lever: zinc-plated steel

Sealing: NBR

Protection rating

IP 65 (latched)

NEMA 250, UL50E: 12, 4 (latched)

VDE-tested

Certified production control: VDE-REG. no.: B437

UL-tested:

UL File Number: E75770

Temperature range

-40°C to +100°C, short-term up to +125°C

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send LAPP / 70135400 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.